



Smart Communication Box

Datasheet



Technical Specifications	Smart Communication Box
Configuration	
Datalogger	Yes
RS485	Yes
DI/DO(Optional)	Yes
PLC module (Optional)	Kehua advanced broadband PLC Technology
Fibre channel switch (Optional)	2 optical ports, 6electrical ports
Splice box(Optional)	2-input, 8/12-output
Anti-PID(Optional)	Kehua advanced Anti-PID technoloty
Maximum No. device	200
Environment	
Operating Temperature Range	-30℃~60℃
Relative Humidity	0%~100%
Max.Operating Altitude	4000m
Electrical	
Input AC Voltage For Cabinet	100V~240V, L/N(L)+PE
Input AC Voltage For PLC Module	300V-900V, 3 Phase
Input AC Frequency	50/60 Hz
Mechanical	
Cable Entries	Bottom in & out
Maintenance	Front
Dimensions(W*H*D)	950*650*280mm
Weight	36kg
IP Degree	IP65
Installation Options	Wall Mounting, Rack Mounting, Pole Mounting

- END -

Kehua Data Co., Ltd.

Add: No. 457, Malong Road, Torch High-Tech Industrial Zone, Xiamen Fujian 361006
China

Tel: +86-592-5160516

Fax: +86-592-5162166

Email: Intertrade@kehua.com